

•		25X1
	Approved For Release 2002/06/17 : CIA-RDP78B04767A000400050006-5	
	TOP SECREL	
		25X1
		25X1
1	2.3 EVALUATION AT LOW SOLAR ALTITUDES	
	2.3.1 Test Type	
the second		25X1
	2.3.2 Test Objectives	
		25X1
	1. Examine the color reproduction at low solar	
	altitudes.	
	2. Obtain an estimate of the image quality obtainable with	
· -		
	this material.	
	3. Consider theimpact on the performance of the	25X1
• •	Tall up Court and	
	KH-D System.	
7	2.3.3 Test Details	
	The photography from this test was obtained	25X1
	at 65,000 feet. This resulted in scale	25X1
•	at 05, 000 feet. This resulted in scale	051/4
	of 33,000% at the center of format for the original negatives.	25X1
		25X1
		25X1
	The flight started early in the morning	20/(1
	in order to acquire photography at very low solar altitudes. The	. •
	photography continued from 5 degrees solar altitude to midmorning	
	where the solar altitude was 37 degrees. In order to obtain well	•
	exposed photography over this wide range of solar altitudes, a neutral	
	lensity filter was used in one unit to make a full stop difference in	•
	exposure between the two cameras. The specific camera parameters	
Oeclass Revi	iew by NIMA / DoD	25X1
Pediass IVEAL	The state of the s	OEV4
	Approved For Release 2002/06/17 : CIA-RDP78B04 767A000400050006-5	25X1
_	• •	

 	-
) E	V A
 (3)	Λī

for the flight are listed in Table 2.3-1.

• ·
.5X1
*. · · · · · · · · · · · · · · · · · · ·

2.3.4 Discussion of Examples

Two photographic illustrations have been included to show the resultant photography at the extremes of the solar altitudes covered. (See Fig. 2.3-2). These illustrations have been printed to look as much like the original film as possible. It is interesting to note that in making these images many of the test prints had a much better color balance. However, they were not used since they were not a good representation of the original material.

25X1

At the low solar altitude, sufficient quality is present to clearly locate small aircraft. There is little improvement in the recognition of these aircraft (or support vehicles) at the higher solar elevation. The overall color cast of the material at low solar altitude is bluish. However, there are areas of warm tone where the sunlight strikes the area directly. In the shadow areas, such as near wooded terrain, there is a severe loss due to underexposure.

At the higher solar altitudes the image has a warm tone cast, principally brown. Almost the entire scene is illuminated by direct sunlight. As such, there is detail prevalent in the wooded areas. High reflectance objects are really not that much easier to identify and recognize. This can be noted in the light aircraft, the terminal area, the swimming pool, and the parking lot.

2.3.5 Results/Condlusions

The following results and conclusions were obtained from this evaluation:

- can generally be used at solar altitudes as low as 10 degrees. Certain types of information can recorded as low as 5 degrees solar altitude.
- could be properly exposed at a range 2. A full load of solar altitudes as low as 13 degrees in the KH-4B System. Only slight underexposure would occur at 10 degrees.

25X1

25X1

25X1

25X1

Approved For Release 2002/06/17: CIA-RDP78B04767A000400050006-5

Approved For Release	2002/06/17 CIA-RDP78B04	767A000480030006-5
	ior segmen	PAPED
!	•	1

A partial load, however, would be more severely limited since a combination of filter and exposure control would have to be used with the color correction filter inthis case. A neutral density filter would have to be used since the film is approximately 8 x faster and slit control alone is

25X1

not sufficient for proper exposure.

25X1

25X1

25X1

lins is not optimized for the entire visible spec-3. The The 2:1 resolution performance to be expected from a solit load is 40 to 50 lines per The resolution expected from a full load

25X1 25X1

where the lens can be set at peak focus for this approximated material, is from 50 to 60 lines per millimeter. It would

be worth considering a lens design corrected for the entire visible wavelength band if color is to be used extensively

in the KH-4B System.

Color reproduction is poor at the low solar altitudes when ising the nominal color compensating filter pack. For a full load where both prime and alternate filters/can be devoted to the color film a separate filter pack should be used at low solar altitudes. However, this is not practical for a partial load of color film since one filter would have to be used with black and white emulsion.

Poor color balance (from either improper filtration, inadequate

Approved For Release 2002/06/17: CIA-RDP78B04767A060400050006-5 in the duplication stage.

The blue component on the color image is severely affected by atmospheric haze, resulting in very low contrast. A stronger haze cutting filter (such as the Wratten no. 4) would be useful in improving the contrast. There must be, though, an appropriate color correction filter used to off-set the yellow cast that would result in the highlights.

25X1

25X1